



# Bearing Grease

## K-Supply

K-Supply Bearing Grease NLGI N2 is suitable for multiple purposes. It is resistant to oxidation, adhesive and highly resistant to pressure. K-Supply Bearing Grease has a special additivation for the lubrication of the roller and slide bearings for temperatures from -20°C up to +120°C.

This product which has been tested and approved at the Komori Graphic Center Europe in Utrecht is especially suited for high points of lubrication with high centrifugal losses.

### Benefits

- Suitable for points of lubrication with high centrifugal losses.
- Grease can be used up to a speed factor (ndm\*) of about 400.000.
- Resistant to oxidation, adhesive and highly resistant to pressure.
- Multipurpose grease.

### Directions

Storage conditions are 15 - 25°C.

Keep away from sources of ignition.

Suitable packaging; only to be kept in original packaging.

For safety measurements, use hand and eye protection and wear protective clothing.

For safe handling instructions please check MSDS.

### Specifications

Product name	K-Supply Bearing Grease	
Characterisation	KP2K-20	DIN 51 502
ISO VG	100	
Colour	Beige	
Chemical composition	Mineral oil, Lithium soap, additives	
Water resistance:	(0-1)-90	DIN 51 807-1
NLGI Class	2	
Dropping point	> 180° C	DIN ISO 2176
Oil separation	< 2	DIN 51 817
Base oil viscosity at 40°C (mm <sup>2</sup> /s)	100 ± 10%	DIN ISO 3448
Packaging	400 Gr. Cartridge 25 x 400 Gr. Cartridge	