



Fluid Grease H1

Elkalub

K-Supply

K-Supply Fluid Grease H1 NLGI N00 is a grease for application in the food industry. The product is adhesive and is suitable for sterilizers, spindles, valves, gears, slow-turning ball bearings, slip motions and for the lubrication of chains.

This product which has been tested and approved at the Komori Graphic Center Europe in Utrecht shows a good resistance to water (up to +100°C) as well as alkalis and acids.

Benefits

- For application in the food industry.
- Suitable for temperatures from -10°C up to +130°C (short time up to 180°C).

Directions

Storage conditions are 15 - 25°C .

Keep away from sources of ignition.

Suitable packaging; only to be kept in original packaging.

For safety measurements, use hand and eye protection and wear protective clothing.

For safe handling instructions please check MSDS.

Specifications

Product name	K-Supply Fluid Grease	
Chemical composition	white oil, synthetic oil, inorganic thickener, additives	
Classification	KP00K-10	DIN 51 825
Appearance	brown, transparent grease	
Upper operating temperature [°C]	130	
Lowest operating temperature [°C]	-10	
Short-term operating temperature [°C]	180	
NLGI-grade	00	DIN 51 818
Base oil viscosity at 40°C [mm ² /s]	185	DIN ISO 3448
Water resistance	(0-1)-90	DIN 51 807
Oil separation (K) [%]	<2	DIN 51 817
Oil separation (N) [%]	<6	DIN 51 817
Registration no. (H1)	133174	
Packaging	2 Kg Bag 6 x 2 Kg Bag	