



# Mineral Gear Oil

## K-Supply

K-Supply Mineral Gear Oil is a high-performance ready-for-use mineral oil based lubricant. It offers high protection against wear and corrosion and has an excellent load carrying ability. The extension of the oil changing intervals increases the availability of the machines and considerably reduces oil consumption (environmental aspect) K-Supply Mineral Gear Oil is exempt from PCB and chlorine products and can be disposed of as regular used oils.

This product which has been tested and approved at the Komori Graphic Center Europe in Utrecht guarantees a long service life and safe operation because of special inhibitors against ageing.

### Benefits

- Exempt from PCB.
- Exempt from chlorine products.
- Can be disposed of as regular used oils.
- Long service life and safe operation.

### Directions

Storage conditions are 15 - 25°C.

Keep away from sources of ignition.

Suitable packaging; only to be kept in original packaging.

For safety measurements, use hand and eye protection and wear protective clothing.

For safe handling instructions please check MSDS.

Use according to the viscosity prescriptions of the Komori press.

### Specifications

Product name	K-Supply Mineral Gear Oil	
ISO VG	68	
Viscosity at 25°C (mm <sup>2</sup> /s)	147,9	
Viscosity at 40°C (mm <sup>2</sup> /s)	68	
Viscosity at 110°C (mm <sup>2</sup> /s)	8,6	
SHELL 4 Ball Welding load	> 2200N	DIN 51 350
Packaging	20 Ltr Can	