



# Mineral Gear Oil

## for GL837P

# K-Supply

K-Supply Mineral Gear Oil for GL837P is a high-performance ready-for-use mineral oil based lubricant. It offers high protection against wear and corrosion and has an excellent load carrying ability. The extension of the oil changing intervals increases the availability of the machines and considerably reduces oil consumption (environmental aspect) K-Supply Mineral Gear Oil is exempt from PCB and chlorine products and can be disposed of as regular used oils.

This product which has been tested and approved at the Komori Graphic Center-Europe in Utrecht guarantees a long service life and safe operation because of special inhibitors against ageing.

### Benefits

- Exempt from PCB
- Exempt from chlorine products
- Can be disposed of as regular used oils
- Long service life and safe operation
- High protection against wear and corrosion
- Prevention of electrostatic charge
- High absorption capacity for condensed water
- Good dirt dispersing ability
- Finely filtered for minimal wear
- Tested and approved by the Komori Graphic Center-Europe

### Directions

Storage conditions are 15 - 25°C.

Keep away from sources of ignition.

Suitable packaging; only to be kept in original packaging.

For safety measurements, use hand and eye protection and wear protective clothing.

For safe handling instructions please check MSDS.

Use according to the viscosity prescriptions of the Komori press.

### Specifications

Product name	K-Supply Mineral Gear Oil
ISO VG	32
State	Liquid
Colour	Pale yellow
Odour	Characteristic odour
Solubility in water	Insoluble
Flash point°C	> 160
Viscosity at 25°C (mm <sup>2</sup> /s)	59,5
Viscosity at 40°C (mm <sup>2</sup> /s)	32
Viscosity at 110°C (mm <sup>2</sup> /s)	5,7
Relative density	~ 0,87 g/cm <sup>3</sup> (25 °C)
Vapour pressure	< 0,1 hPa/20°C
Application	P, H, G
Packaging	20 Ltr Can